

TEC 20

Efficient bagging



DESCRIPTION

The **TEC 20** is designed for bagging parts in medium or large series.

Efficient and compact, it is available in the following versions

- **Inclined**, to slow down the fall of the products.
- **Vertical**, for a gain in speed.
- **Horizontal**, with a system of assisted introduction keeping the direction of orientation of the parts, ideal for the fragile products.

INNOVATIVE

Human/machine touch interface oriented **Industry 4.0** to :

- *Maintain*
- *Visualize / Report*
- *Exploit / Inform*




MADE
IN FRANCE


FUNCTIONING

The **TEC 20** operates from a voltage-regulated flat film reel.


- 1** The film is conformed around a tube, called "conformer"
- 2** The parts are introduced into the conformator in manual or automatic mode
- 3** The longitudinal sealing unit seals the film during its translation
- 4** The cross-sealing unit seals the bottom and top of the bags simultaneously and separates them




The conformer forms the bag in its width



This principle avoids any risk of loss of parts




Formation of the bag in its length




PERFORMANCE

- ⇒ Low loading height
- ⇒ Easy to move, machine mounted on wheels
- ⇒ Programmable controller
- ⇒ "BRUSHLESS" motorization
- ⇒ Touch screen and color man-machine interface
- ⇒ Production counter
- ⇒ Transverse welding



Impulse welding
Jaws equipped with welding wires



Thermal welding
Grooved and heated jaws

- ⇒ Continuous longitudinal welding
- ⇒ Motorized quick release coil holder
- ⇒ Marking in real time according to the length of the bag

OPTIONS & ACCESSORIES

- ⇒ Manual loading table
- ⇒ Identification by direct printing on thermal transfer film and/or application of labels
- ⇒ Heavy parts receiving flap
- ⇒ Monobloc conformator
- ⇒ Bag vibrator to standardize the parts
- ⇒ Thermal welding

Possible synchronization with other devices :

- Robot
- Conveyor belt for product supply
- Automatic counting machine
- Bag weight control
- Automatic boxing



PACKING MATERIALS

- 🌿 Biodegradable Oxo film
- 🌿 Biodegradable film type PLA
- 🌿 Paper
- ⇒ PE film
- ⇒ Neutral or pre-printed film


GREEN SOLUTIONS




Our machines allow for 100% ecological, biosourced, recyclable and biodegradable plastics or paper sleeves.

BAG SHAPES

ASYMETRICAL CUSHION BAG



OPTIONAL



TECHNICAL CHARACTERISTICS

		Version 300	Version 400
Maximum speed		Up to 40 bags/min (Depending on film type, quality, thickness ...)	
Bag weight		Up to 600 grams (Higher weight with receiving flap)	
Bag size	Width	80 to 300 mm	80 to 400 mm
	Length	Adjustment at will from mm to mm	
	Head opening Optional	100 mm 150 mm	100 mm 150 to 200 mm
Coil size		Diameter : 320 mm	
Packing materials		Complex or thermo welding material Thickness : 60 to 150µ	
Power supply		220 V single-phase 50hz / 6 bars	
Machine weight		About 400 kg	

